



Color: ■ light gray

Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	800 V
Rated impulse voltage (III/3)	8 kV
Rated current	25 A

Physical data

Width	29.5 mm / 1.161 inches
Height	4.1 mm / 0.161 inches
Depth	19 mm / 0.748 inches
Jumper assignment	1-2 3-4 5-6

Material data

Note (material data)	Information on material specifications can be found here
Color	light gray
Fire load	0.021 MJ
Weight	2.7 g

Commercial data

eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	25 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143687454
Customs tariff number	85366990990



Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 2002-406/020-000	↓

Documentation

Bid Text			
2002-406/020-000	19.02.2019	xml 2.54 KB	↓
2002-406/020-000	27.04.2017	doc 23.50 KB	↓


CAD/CAE-Data

CAD data	
2D/3D Models 2002-406/020-000	↓

CAE data	
EPLAN Data Portal 2002-406/020-000	↓
WSCAD Universe 2002-406/020-000	↓
ZUKEN Portal 2002-406/020-000	↓

Installation Notes

Commoning



This delta jumper has been specially developed to create a delta configuration and is used on motor terminal boards equipped with rail-mount terminal blocks TOPJOB® S.