



Color: ■ black

| Notes | |
|--------------------|---|
| Safety information | Push down the wire jumper until fully inserted! |

Electrical data

| Ratings per IEC/EN | |
|-------------------------------|-------|
| Nominal voltage (III/3) | 800 V |
| Rated impulse voltage (III/3) | 8 kV |
| Rated current | 18 A |

Connection data

| Connection 1 | |
|-----------------|---------------------|
| Solid conductor | 1.5 mm ² |

Mechanical data

| | |
|-----------------------------|--------|
| Wire length of wire jumpers | 110 mm |
|-----------------------------|--------|

Material data

| | |
|----------------------|--|
| Note (material data) | Information on material specifications can be found here |
| Color | black |
| Fire load | 0 MJ |
| Weight | 3.1 g |



| Commercial data | | |
|-----------------------|--------------------------------|--|
| Product Group | 2 (Terminal Block Accessories) | |
| eCl@ss 10.0 | 27-14-11-40 | |
| eCl@ss 9.0 | 27-14-11-40 | |
| ETIM 8.0 | EC000489 | |
| ETIM 7.0 | EC000489 | |
| PU (SPU) | 100 (10) pcs | |
| Packaging type | Box | |
| Country of origin | DE | |
| GTIN | 4045454302245 | |
| Customs tariff number | 85444290900 | |

| Environmental Product Compliance | | |
|----------------------------------|------------------------|--|
| RoHS Compliance Status | Compliant,No Exemption | |

Downloads

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 2009-414

↓

| Documentation | | | | |
|---------------|------------|-----|----------|---|
| Bid Text | | | | |
| 2009-414 | 19.02.2019 | xml | 2.77 KB | ↓ |
| 2009-414 | 28.04.2017 | doc | 24.00 KB | ↓ |

| CAD/CAE-Data | | |
|----------------------------|---|--|
| CAE data | | |
| EPLAN Data Portal 2009-414 | ↓ | |
| WSCAD Universe 2009-414 | ↓ | |

| Installation Notes | |
|--------------------|--|
| Commoning | |



Push down the wire jumper until fully inserted. Lift the jumper with an operating tool for rewiring.

Commoning



Push-in type wire jumpers common terminal blocks over longer distances and across multiple levels.