



Color: ■ orange

| Physical data |                       |
|---------------|-----------------------|
| Width         | 9.6 mm / 0.378 inches |

| Material data               |                                                                          |
|-----------------------------|--------------------------------------------------------------------------|
| Note (material data)        | <a href="#">Information on material specifications can be found here</a> |
| Color                       | orange                                                                   |
| Material group              | I                                                                        |
| Insulation material         | Polyamide (PA66)                                                         |
| Flammability class per UL94 | V0                                                                       |
| Fire load                   | 0.024 MJ                                                                 |
| Weight                      | 0.8 g                                                                    |



| Commercial data       |                   |
|-----------------------|-------------------|
| Product Group         | 18 (X-COM-System) |
| eCl@ss 10.0           | 27-14-11-92       |
| eCl@ss 9.0            | 27-14-11-92       |
| ETIM 8.0              | EC002848          |
| ETIM 7.0              | EC002848          |
| PU (SPU)              | 100 (25) pcs      |
| Packaging type        | Box               |
| Country of origin     | DE                |
| GTIN                  | 4045454732776     |
| Customs tariff number | 85389099990       |

| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

| Downloads                                 |                   |
|-------------------------------------------|-------------------|
| Environmental Product Compliance          |                   |
| Compliance Search                         |                   |
| Environmental Product Compliance 2022-152 | <a href="#">↓</a> |

| Documentation |            |     |          |                   |
|---------------|------------|-----|----------|-------------------|
| Bid Text      |            |     |          |                   |
| 2022-152      | 30.01.2017 | doc | 23.50 KB | <a href="#">↓</a> |
| 2022-152      | 19.02.2019 | xml | 2.50 KB  | <a href="#">↓</a> |

| CAD/CAE-Data          |                         |
|-----------------------|-------------------------|
| CAD data              | CAE data                |
| 2D/3D Models 2022-152 | WSCAD Universe 2022-152 |
| <a href="#">↓</a>     | <a href="#">↓</a>       |
|                       | ZUKEN Portal 2022-152   |
|                       | <a href="#">↓</a>       |

| Installation Notes                                                                  |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Locking system                                                                      |                                                                                     |
|  |  |
| Slide the locking lever into position.                                              | Female plugs can be individually locked.                                            |