



Color: ■ light gray

Similar to illustration



Dimensions in mm
L = pole no. x pin spacing
A = 3.6 mm THT solder pin
A = 2.4 mm THR solder pin



- Universal connection for all conductor types
- Simple, push-in termination of solid and ferruled conductors
- Easy-to-use design does not require special tools
- Ability to wire while mated or unmated
- Integrated test ports for testing parallel to conductor entry
- Custom-installed solder pins

Notes

Safety information

The **picoMAX® Pluggable Connection System** includes connectors without breaking capacity in accordance with DIN EN 61984. When used as intended, these connectors must not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.

Electrical data				
Ratings per		IEC/EN 60664-1		
Overvoltage category		III	III	II
Pollution degree		3	2	2
Nominal voltage		160 V	160 V	320 V
Rated surge voltage		2.5 kV	2.5 kV	2.5 kV
Rated current		10 A	10 A	10 A

Approvals per		UL 1059		
Use group		B	C	D
Rated voltage		300 V	-	300 V
Rated current		10 A	-	10 A



Connection data

Connection points	2	Connection 1	
Total number of potentials	2	Connection technology	Push-in CAGE CLAMP®
Number of connection types	1	Actuation type	Push-button
Number of levels	1	Actuation direction 1	Operation parallel to conductor entry
		Solid conductor	0.2 ... 1.5 mm² / 24 ... 14 AWG
		Fine-stranded conductor	0.2 ... 1.5 mm² / 24 ... 14 AWG
		Fine-stranded conductor; with insulated ferrule	0.25 ... 0.75 mm²
		Fine-stranded conductor; with uninsulated ferrule	0.25 ... 1.5 mm²
		Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
		Conductor connection direction to PCB	0 °
		Pole number	2

Physical data

Pin spacing	Pin spacing	3.5 mm / 0.138 inches
Width	Width	7 mm / 0.276 inches
Height	Height	11.4 mm / 0.449 inches
Depth	Depth	14 mm / 0.551 inches
Solder pin length	Solder pin length	3.6 mm
Solder pin diameter	Solder pin diameter	1 mm
Drilled hole diameter with tolerance	Drilled hole diameter with tolerance	1.2 (+0.1) mm

Mechanical data

Variable coding	Variable coding	No
Anti-rotation protection	Anti-rotation protection	Yes

Plug-in connection

Contact type (pluggable connector)	Contact type (pluggable connector)	Female connector/socket
Connector (connection type)	Connector (connection type)	for PCB
Mismating protection	Mismating protection	No
Plugging without loss of pin spacing	Plugging without loss of pin spacing	Yes
Mating direction to the PCB	Mating direction to the PCB	0 °

PCB contact

PCB contact	PCB contact	THT
-------------	-------------	-----

Material data

Note (material data)	Note (material data)	Information on material specifications can be found here
Color	Color	light gray
Material group	Material group	I
Insulation material	Insulation material	Polyphthalamide (PPA GF)
Flammability class per UL94	Flammability class per UL94	V0
Clamping spring material	Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Contact material	Electrolytic copper (E _{cu})
Contact plating	Contact plating	Tin
Fire load	Fire load	0.021 MJ
Weight	Weight	1.1 g



Environmental requirements	
Limit temperature range	-60 ... +100 °C
Processing temperature	-35 ... +60 °C

Commercial data	
Product Group	26 (picoMAX Connectors)
eCl@ss 10.0	27-44-04-02
eCl@ss 9.0	27-44-04-02
ETIM 8.0	EC002637
ETIM 7.0	EC002637
PU (SPU)	200 pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821162865
Customs tariff number	85366990990

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
CB DEKRA Certification B.V.	IEC 61984	NL-49736/A1
CSA DEKRA Certification B.V.	C22.2	2362521
CSA DEKRA Certification B.V.	C22.2 No. 158	2362521
KEMA/KEUR DEKRA Certification B.V.	EN 61984	71-102260 REV.1
UL Underwriters Laboratories Inc.	UL 1977	E45171

Downloads



Environmental Product Compliance



Compliance Search	
Environmental Product Compliance 2091-1372	

Documentation

Additional Information			
Technical Section	03.04.2019	pdf 2027.26 KB	

CAD/CAE-Data

CAD data	CAE data
2D/3D Models 2091-1372 	ZUKEN Portal 2091-1372 

PCB Design	
Symbol and Footprint via SamacSys 2091-1372 	
Symbol and Footprint via Ultra Librarian 2091-1372 	

1 Compatible Products

1.1 Optional Accessories

1.1.1 Coding



1.1.1.1 Coding



Item No.: [2091-1610](#)
Coding key carrier; suitable for 3.5 mm pin spacing; orange

Installation Notes

Conductor termination



Terminating fine-stranded conductors and removing all conductor types via push-buttons.

Solid and ferruled conductors are terminated by simply pushing them into unit.

Marking



Pole marking via direct marking perpendicular to conductor entry.

Pole marking via factory direct marking.

Testing



Testing via 1 mm Ø test pin – touch contact.