



Color: ■ light gray

Similar to illustration

Physical data		
Pin spacing		5/5.08 mm

Mechanical data		
Suitable		for male connectors

Material data		
Note (material data)		Information on material specifications can be found here
Color		light gray
Material group		I
Insulation material		Polyamide (PA66)
Flammability class per UL94		V0
Fire load		0.004 MJ
Weight		0.2 g

Commercial data		
Product Group		3 (Multi Conn. System)
eCl@ss 10.0		27-14-11-92
eCl@ss 9.0		27-14-11-92
ETIM 8.0		EC002848
ETIM 7.0		EC002848
PU (SPU)		200 (100) pcs
Packaging type		Box
Country of origin		DE
GTIN		4017332117371
Customs tariff number		39269097900

RoHS Compliance Status	Compliant, No Exemption
Compliant, No Exemption	

General approvals



Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2	1466354

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 231-129



Documentation

Additional Information

Technical Section	pdf	
03.04.2019	2027.26 KB	

CAD/CAE-Data

CAD data

2D/3D Models 231-129




CAE data

ZUKEN Portal 231-129



Installation Notes

Coding



Coding a male header – fitting coding key (s).

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com