

Jumper; for conductor entry; 3-way; insulated; gray



Similar to illustration

Ratings per	IEC/EN 60664-1		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	-	320 V	-
Rated surge voltage	-	4 kV	-
Rated current	-	16 A	-

Connection 1	
Pole number	3

Pin spacing	5/5.08 mm / 0.197/0.2 inches
Width	15.3 mm / 0.602 inches
Depth	6.15 mm / 0.242 inches
Jumper assignment	1-2-3

Suitable for male and female connectors with CAGE CLAMP® connection

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.008 MJ
Weight	0.7 g



Commercial data		
Product Group	3 (Multi Conn. System)	
eCl@ss 10.0	27-14-11-40	
eCl@ss 9.0	27-14-11-40	
ETIM 8.0	EC000489	
ETIM 7.0	EC000489	
PU (SPU)	100 (25) pcs	
Packaging type	Box	
Country of origin	DE	
GTIN	4045454565848	
Customs tariff number	85366990990	

Environmental Product Compliance		
RoHS Compliance Status	Compliant, No Exemption	

Approvals / Certificates		
General approvals		





Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2	1466354

Downloads		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 231-903		

Documentation			
Additional Information			
Technical Section	03.04.2019	pdf 2027.26 KB	

Installation Notes	
Installation	




- Notice: Insert jumper bar according to direction of symbols.

□ symbol correlates to the direction of the operating slot.
- Notice: Insert jumper bar according to direction of symbols.


○ symbol shows direction to conductor entry.

## Coding



Custom comb-style jumper bars are created by breaking off jumper contacts (3 contacts and more).

## Installation




Notice: Comb-style jumper bars reduce the conductor cross-section to 1.5 mm<sup>2</sup> "s" + "f-st."

## Commoning



Inserting a comb-style jumper bar via multipole operating tool – with the female or male connector being supported in a suitable holding device.

## Installation



Operating tool for comb-style jumper bars (231-902)

## Application



Both male and female connectors can be pre-assembled with comb-style jumper bars upon request.