



Color: ■ gray

Electrical data

Ratings per IEC/EN	
Rated current	10 A

Physical data

Width	8 mm / 0.315 inches
Height	10 mm / 0.394 inches
Depth	4 mm / 0.157 inches
Jumper assignment	1-2

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.006 MJ
Weight	0.4 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C



Commercial data		
Product Group	9 (Std Chassis Mt Blocks)	
eCl@ss 10.0	27-14-11-40	
eCl@ss 9.0	27-14-11-40	
ETIM 8.0	EC000489	
ETIM 7.0	EC000489	
PU (SPU)	500 (25) pcs	
Packaging type	Box	
Country of origin	PL	
GTIN	4045454030858	
Customs tariff number	85366990990	

Environmental Product Compliance		
RoHS Compliance Status	Compliant,No Exemption	

Downloads		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 260-402		

Documentation				
Bid Text				
260-402	19.02.2019	xml 2.62 KB		
260-402	17.08.2017	doc 23.50 KB		


CAD/CAE-Data				
CAD data		CAE data		
2D/3D Models 260-402		EPLAN Data Portal 260-402		
		WSCAD Universe 260-402		
		ZUKEN Portal 260-402		

1 Compatible Products
1.1 Optional Accessories
1.1.1 Tool
1.1.1.1 Operating tool



Item No.: 209-132
Operating tool; for connecting comb-style jumper bar; made of insulating material; 2-way; natural

Installation Notes
Commoning



Commoning with comb-style jumper bar.