



Color: ■ gray

Notes	
Safety information	Always push voltage tap down into the terminal block until fully inserted!

Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	800 V
Rated impulse voltage (III/3)	8 kV
Rated current	24 A

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	15.474 MJ
Weight	22.1 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C



Commercial data		
Product Group	1 (Rail Mounted Terminal Blocks)	
eCl@ss 10.0	27-14-11-92	
eCl@ss 9.0	27-14-11-92	
ETIM 8.0	EC002848	
ETIM 7.0	EC002848	
PU (SPU)	25 pcs	
Packaging type	Box	
Country of origin	DE	
GTIN	4044918853408	
Customs tariff number	85366990990	

Environmental Product Compliance		
RoHS Compliance Status	Compliant,No Exemption	

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 283-407

↓

Documentation				
Bid Text				
283-407	19.02.2019	xml	2.81 KB	↓
283-407	02.05.2017	doc	22.50 KB	↓

CAD/CAE-Data		
CAE data		
EPLAN Data Portal 283-407	↓	
WSCAD Universe 283-407	↓	

Installation Notes

Power tap



Always push voltage tap (283-407) down into the terminal block until fully inserted!

