

Color: ■ gray

Electrical data

Ratings per IEC/EN		Ex information	
Rated current	232 A	Rated current (Ex e II)	211 A

Physical data

Jumper assignment	1-2
-------------------	-----

Material data

Note (material data)		Information on material specifications can be found here
Color	gray	
Fire load	0.162 MJ	
Weight	55 g	



Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918269490
Customs tariff number	85366990990




Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption



Approvals / Certificates

General approvals			Approvals for hazardous areas		
					
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2	154112	AEx Underwriters Laboratories Inc.	UL 60079	E185892 (AEx eb II C resp. Ex eb II C)





Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 285-495	

Documentation

Bid Text			
285-495	19.02.2019	xml 2.62 KB	
285-495	04.01.2018	doc 22.50 KB	

CAD/CAE-Data

CAD data		CAE data	
2D/3D Models 285-495		EPLAN Data Portal 285-495	
		WSCAD Universe 285-495	
		ZUKEN Portal 285-495	



Installation Notes

Commoning

Commoning with an adjacent jumper: insert the jumper above the conductor entry hole – prior to conductor termination. The nominal cross-section remains unchanged.

Removing jumper via operating tool.