

Data Sheet | Item Number: 734-137/108-000


THT male header; 1.0 x 1.0 mm solder pin; straight; 100% protected against mismatching; Threaded flange; Pin spacing 3.5 mm; 7-pole; light gray

<https://www.wago.com/734-137/108-000>



Color: ■ light gray


Similar to illustration



Dimensions in mm

$L = (\text{pole no.} \times \text{pin spacing}) + 9.5 \text{ mm}$

$L1 = (\text{pole no.} \times \text{pin spacing}) + 4.9 \text{ mm}$



- Horizontal or vertical PCB mounting via straight or angled solder pins
- 100% protected against mismatching; only mating halves with the same number of poles can be connected together
- Coding option available

Notes				
Safety information		The MCS – MULTI CONNECTION SYSTEM includes connectors without breaking capacity in accordance with DIN EN 61984. When used as intended, these connectors must not be connected/disconnected when live or under load. When used as intended, these connectors must not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.		

Variants:		Other pole numbers Gold-plated or partially gold-plated contact surfaces Other versions (or variants) can be requested from WAGO Sales or configured at https://configurator.wago.com/ .		
-----------	--	---	--	--

Electrical data				
Ratings per		IEC/EN 60664-1		
Overvoltage category		III	III	II
Pollution degree		3	2	2
Nominal voltage		160 V	160 V	320 V
Rated surge voltage		2.5 kV	2.5 kV	2.5 kV
Rated current		10 A	10 A	10 A
Approvals per		UL 1059		
Use group		B	C	D
Rated voltage		300 V	-	300 V
Rated current		10 A	-	10 A



Approvals per		CSA	
Use group	B	C	D
Rated voltage	300 V	-	300 V
Rated current	10 A	-	10 A

Connection data			
Total number of potentials	7	Connection 1	
Number of connection types	1	Pole number	7
Number of levels	1		

Physical data		
Pin spacing	3.5 mm / 0.138 inches	
Width	34 mm / 1.339 inches	
Height	14.8 mm / 0.583 inches	
Height from the surface	10.3 mm / 0.406 inches	
Depth	8.5 mm / 0.335 inches	
Solder pin length	4.5 mm	
Solder pin dimensions	1 x 1 mm	
Drilled hole diameter with tolerance	1.4 (+0.1) mm	

Mechanical data		
Variable coding	Yes	
Anti-rotation protection	Yes	

Plug-in connection		
Contact type (pluggable connector)	Male connector/plug	
Connector (connection type)	for PCB	
Mismating protection	Yes	
Mating direction to the PCB	90 °	
Locking of plug-in connection	Threaded flange	

PCB contact		
PCB contact	THT	
Solder pin arrangement	over the entire male connector (in-line)	
Number of solder pins per potential	1	

Material data		
Note (material data)	Information on material specifications can be found here	
Color	light gray	
Material group	I	
Insulation material	Polyamide (PA66)	
Flammability class per UL94	V0	
Contact material	Electrolytic copper (E _{CU})	
Contact plating	Tin	
Fire load	0.037 MJ	
Weight	2.4 g	



Environmental requirements	
Limit temperature range	-60 ... +100 °C
Processing temperature	-35 ... +60 °C

Commercial data	
Product Group	3 (Multi Conn. System)
eCl@ss 10.0	27-44-04-02
eCl@ss 9.0	27-44-04-02
ETIM 8.0	EC002637
ETIM 7.0	EC002637
PU (SPU)	100 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454758738
Customs tariff number	85366930000

Environmental Product Compliance	
CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	f80dfc1e-ce01-42dc-8bbb-e73a1ecf2dad
SCIP notification number (Belgium)	75d96169-cf8a-4d12-90bf-cec05925aef4
SCIP notification number (Bulgaria)	9525514b-4011-4445-8b5f-16df5f287ebc
SCIP notification number (Czech Republic)	6f0d481f-a8b5-42fc-8324-252e4ec0de78
SCIP notification number (Denmark)	4fd2e003-f2da-461e-a05e-68173aa67f1e
SCIP notification number (Finland)	a6a416d5-1f66-4e1e-ba04-d007c3107056
SCIP notification number (France)	ff9e6235-56da-45e2-a0b0-8a49496e65f6
SCIP notification number (Germany)	1125b006-54c5-487a-90b7-ddfacddde21e
SCIP notification number (Hungary)	d6a1827d-5010-49a8-bfe1-a5933409c578
SCIP notification number (Italy)	d81db001-1c65-4f0d-bdf2-243afff2f98b
SCIP notification number (Netherlands)	a6c28a94-635b-47f7-b5f9-3ede121b2d4c
SCIP notification number (Poland)	5e5c12f1-24db-45bf-bfb3-08212968e0fe
SCIP notification number (Romania)	21fb8746-3735-4b4e-9587-fb1c0b1c85ae
SCIP notification number (Sweden)	56836a63-1649-4e07-b421-bbc6a1b0f5fa

Approvals / Certificates		
General approvals		
		
Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2	1465035
UL Underwriters Laboratories Inc.	UL 1977	E 45171
UR Underwriters Laboratories Inc.	UL 1059	E45172
Declarations of conformity and manufacturer's declarations		
		
Approval	Standard	Certificate Name
Railway WAGO GmbH & Co. KG	-	Railway Ready



Approvals for marine applications



Approval	Standard	Certificate Name
BV Bureau Veritas S.A.	IEC 60998	11915/D0 BV

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 734-137/108-000



Documentation

Additional Information
Technical Section 03.04.2019 pdf 2027.26 KB



CAD/CAE-Data

CAD data
2D/3D Models 734-137/108-000



CAE data
ZUKEN Portal 734-137/108-000



PCB Design

Symbol and Footprint via SamacSys 734-137/108-000
Symbol and Footprint via Ultra Librarian 734-137/108-000



1 Compatible Products

1.1 System counterpart

1.1.1 Female connector/socket



Item No.: 734-107/107-000
1-conductor female connector; CAGE CLAMP®; 1.5 mm²; Pin spacing 3.5 mm; 7-pole; 100% protected against mismating; Screw flange; 1,50 mm²; light gray



Item No.: 2734-107/107-000
1-conductor female connector; push-button; Push-in CAGE CLAMP®; 1.5 mm²; Pin spacing 3.5 mm; 7-pole; 100% protected against mismating; Screw flange; 1,50 mm²; light gray

1.2 Optional Accessories

1.2.1 Coding

1.2.1.1 Coding




[Item No.: 734-159](#)
Coding key; to be snapped above top level; black



[Item No.: 734-130](#)
Coding key; to be snapped above top level; white

Installation Notes

Coding



Coding a male header – fitting coding key(s).