Data Sheet | Item Number: 734-327

Strain relief plate; for female and male connectors; 6 mm wide; 1 part; gray

https://www.wago.com/734-327

Mechanical data

Suitable

Weight





Similar to illustration

Dimensions in mm

The arrangement of the attachments for cable ties allows single conductors or multi-core cables to be secured in different ways. The width of the cable ties must correspond to the hole dimensions of the strain relief plates shown above.

for standard male and female connectors (2.5 mm; 3.5 mm; 5 mm; 7.5 mm pin spacing)

Physical data	
Width	6 mm / 0.236 inches
Height	1.87 mm / 0.074 inches
Depth	19.5 mm / 0.768 inches

Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Fire load	0.006 M.I

0.1 g

Commercial data	
Product Group	3 (Multi Conn. System)
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	100 (25) pcs
Packaging type	Вох
Country of origin	DE
GTIN	4017332650328
Customs tariff number	85389099990

Data Sheet | Item Number: 734-327

https://www.wago.com/734-327



Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Approvals / Certificates

Approvals for marine applications



Approval Standard **Certificate Name**

IEC 61984 96/20035 (E5)

Lloyds Register

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product

Compliance 734-327

Documentation

Additional Information

pdf 2027.26 KB **Technical Section**

03.04.2019

Bid Text

734-327

734-327

19.02.2019

27.04.2017

xml 2.49 KB

doc 23.50 KB

CAD/CAE-Data

CAD data

2D/3D Models 734-327

CAE data

ZUKEN Portal 734-327

Installation Notes

Installation



Strain relief plates for factory or in-thefield assembly

Data Sheet | Item Number: 734-327

https://www.wago.com/734-327

MAGO

Application



Strain relief plate, for factory assembly 1-conductor female connector, 2.5 mm pin spacing, light gray, 12-pole, with strain relief plate 733-112/034-000

Application



Strain relief plate, for factory assembly 1-conductor female connector, 2.5 mm pin spacing, light gray, 2-pole, with strain relief plate (733-102/032-000)

Subject to changes. Please also observe the further product documentation!