



Color: ■ silver-colored Similar to illustration

Electrical data

Ratings per IEC/EN	
Rated current	76 A

Physical data

Pin spacing	15 mm / 0.591 inches
Jumper assignment	1-2

Mechanical data

Suitable	for 745 Series (16 mm²) and 2716 Series
----------	---

Material data

Note (material data)	Information on material specifications can be found here
Color	silver-colored
Contact material	Copper alloy
Contact plating	Tin
Fire load	0 MJ
Weight	3.9 g


Commercial data

Product Group	4 (Printed Circuit Connectors)
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	200 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4045454149758
Customs tariff number	85366990990

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads


Environmental Product Compliance


Compliance Search	
Environmental Product Compliance 745-632	

Documentation




Additional Information			
Technical Section	03.04.2019	pdf 2027.26 KB	

CAD/CAE-Data

CAD data	
2D/3D Models 745-632	

CAE data	
ZUKEN Portal 745-632	

Installation Notes



Inserting a comb-style jumper bar.	To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.	To remove the jumper bar, lift it up using a screwdriver – 745 Series.
------------------------------------	--	--