

Data Sheet | Item Number: 770-121

Locking lever; for flying leads; for manual operation; white

<https://www.wago.com/770-121>



Color: ■ white

Locking system WINSTA® MIDI

When using the locking system from the WINSTA® MIDI product line, straightforward installation is ensured. An extensive range of accessories rounds out the WINSTA® product line from WAGO. Our WINSTA® MIDI product line guarantees flexibility for the installation. Through its Push-in CAGE CLAMP® spring pressure connection technology, it achieves error-free, time-saving installation and offers customization for meeting all installation requirements.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This saves time, lowers costs, and reduces the need for servicing. Enjoy the benefits of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with with protection against mismatching from WAGO.

- simple circuits
- fast, secure installation

Connection data

Connection 1

| | |
|----------------|-----------------------|
| Actuation type | Finger-operated lever |
|----------------|-----------------------|

Mechanical data

| | |
|----------|-------------------------------------|
| Suitable | for flying leads; manually operated |
|----------|-------------------------------------|

Material data

Note (material data)

[Information on material specifications can be found here](#)

| | |
|-----------------------------|------------------|
| Color | white |
| Insulation material | Polyamide (PA66) |
| Flammability class per UL94 | V0 |
| Fire load | 0.017 MJ |
| Weight | 0.6 g |

Environmental requirements

| | |
|--|--|
| Processing temperature | -5 ... +40 °C |
| Continuous operating temperature | -35 ... +85 °C |
| Note on continuous operating temperature | Insulating parts for temperatures ≤ 105 °C |

Commercial data

| | |
|-----------------------|---------------|
| Product Group | 20 (Winsta) |
| eCl@ss 10.0 | 27-44-06-92 |
| eCl@ss 9.0 | 27-44-06-92 |
| ETIM 8.0 | EC002863 |
| ETIM 7.0 | EC002863 |
| PU (SPU) | 100 (25) pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4017332755221 |
| Customs tariff number | 85389099990 |

Environmental Product Compliance

| | |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Approvals / Certificates

General approvals



| Approval | Standard | Certificate Name |
|--|----------|------------------|
| VDE VDE Prüf- und Zertifizierungsinstitut | EN 61535 | 40029808 |

Downloads

Environmental Product Compliance

Compliance Search




| | |
|--|-------------------|
| Environmental Product Compliance 770-121 | ↓ |
|--|-------------------|

Documentation

Bid Text


| | | | |
|---------|------------|-----------------|-------------------|
| 770-121 | 19.02.2019 | xml 2.62 KB | ↓ |
| 770-121 | 11.03.2015 | doc 21.50 KB | ↓ |

CAD/CAE-Data

| CAD data | CAE data |
|--|--|
| 2D/3D Models 770-121  | WSCAD Universe 770-121  |
| | ZUKEN Portal 770-121  |

Installation Notes

Locking system



Locking lever, manually operated:

- Push on locking lever
- Pull the connectors apart