



Color: ■ gray

Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	400 V
Rated impulse voltage (III/3)	6 kV
Rated current	24 A

Physical data

Width	4.5 mm / 0.177 inches
Height	6 mm / 0.236 inches
Jumper assignment	1-2

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.008 MJ
Weight	1.3 g

Commercial data



Product Group	17 (TOP JOB Installation Terminal Blocks)
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918270830
Customs tariff number	85366990990

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 780-452	↓

Documentation			
Bid Text			
780-452	19.02.2019	xml 2.91 KB	↓
780-452	28.04.2017	doc 24.00 KB	↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 780-452	EPLAN Data Portal 780-452 ↓
	WSCAD Universe 780-452 ↓
	ZUKEN Portal 780-452 ↓

Installation Notes	
Commoning	
	
Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!	Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!