




Color: ■ white

Similar to illustration

Technical data	
Marking method	Thermal transfer
Marking	11 ... 20
Marking (number)	10
Marking direction	Horizontal marking
Marking color	black
Marking type	Numbers
Marking differentiation	Consecutive numbers per strip
Delivery form	Marker card
Delivery form configuration	10 strips with 10 markers per card
Flammability class per UL94	V2

Physical data	
Marker/strip width	5 mm
Marker width	5 mm

Mechanical data	
Smear resistance	EN 60998-1:2004

Material data	
Color	white
UV resistance	EN 60068-2-5:2010 Procedure B
Halogen-free	Yes
Weight	8.8 g
Fire load	0.264 MJ



Commercial data		
Product Group	2 (Terminal Block Accessories)	
eCl@ss 10.0	27-14-11-37	
eCl@ss 9.0	27-14-11-37	
ETIM 8.0	EC000761	
ETIM 7.0	EC000761	
PU (SPU)	5 pcs	
Packaging type	Bag	
Country of origin	DE	
GTIN	4017332529709	
Customs tariff number	49119900000	

Environmental Product Compliance		
RoHS Compliance Status	Compliant, No Exemption	

Downloads

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 793-503

↓

Documentation				
Bid Text				
793-503	19.02.2019	xml 2.72 KB	↓	
793-503	29.11.2018	doc 23.50 KB	↓	

Installation Notes

Application



Separating a strip from the WMB or WMB marker card.



Stretching a WMB marker strip.



Separating an individual marker from the WMB marker strip – for larger terminal blocks.



Snapping a marking strip into the marker slot.

Marking



Snapping a WMB marker strip into the marker slot of the double marker carrier.



Snapping a marking strip into the marker slot.