



Color: silver-colored

Electrical data

Ratings per IEC/EN		Ratings per UL	
Nominal voltage (III/3)	1000 V	Rated voltage UL (Use Group B)	1000 V
Rated current	125 A	Rated current UL (Use Group B)	130 A
		Rated voltage UL (Use Group C)	1000 V
		Rated current UL (Use Group C)	130 A
		Rated voltage UL (Use Group D)	1000 V
		Rated current UL (Use Group D)	130 A

Ratings per CSA	
Rated voltage CSA (Use Group B)	1000 V
Rated current CSA (Use Group B)	115 A
Rated voltage CSA (Use Group C)	1000 V
Rated current CSA (Use Group C)	115 A
Rated voltage CSA (Use Group D)	1000 V
Rated current CSA (Use Group D)	115 A

Material data

Note (material data)		Information on material specifications can be found here
Color	silver-colored	
Fire load	0 MJ	
Weight	14.4 g	



Commercial data	
ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	10 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143941907
Customs tariff number	85366990990

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 884-3542	

CAD/CAE-Data

CAD data	
2D/3D Models 884-3542	

CAE data	
EPLAN Data Portal 884-3542	
ZUKEN Portal 884-3542	