

Data Sheet | Item Number: 887-803
Splicing Connector Set; L-BOXX MICRO; 221 Series

<https://www.wago.com/887-803>



This item includes:



Item No.: 221-412

Splicing connector with levers; for all conductor types; max. 4 mm²; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

Item No.: 221-413

Splicing connector with levers; for all conductor types; max. 4 mm²; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

Item No.: 221-415

Splicing connector with levers; for all conductor types; max. 4 mm²; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

8

Item No.: 221-2411

Inline splicing connector with levers; for all conductor types; max. 4 mm²; 2-conductor; transparent housing; Transparent cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

30

Material data

Note (material data)

[Information on material specifications can be found here](#)

Fire load

5.642 MJ

Weight

412.1 g

Commercial data

ETIM 8.0	EC000446
PU (SPU)	1 pcs
Country of origin	DE
GTIN	4066966194883
Customs tariff number	85369010000

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 887-803

