



This item includes:

|                                                                                                                                                                                                  |                                                                                                                                                                                                      |                                                                                                                                                                                                  |                                                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                 |                                                                                                                     |                                                                                                                 |                                                                                                            |
| <a href="#">Item No.: 2773-402</a>                                                                                                                                                               | <a href="#">Item No.: 2773-408</a>                                                                                                                                                                   | <a href="#">Item No.: 2773-403</a>                                                                                                                                                               | <a href="#">Item No.: 2773-404</a>                                                                                                                                                            |
| PUSH WIRE® splicing connector; for solid and stranded conductors; max. 4 mm²; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent  | PUSH WIRE® splicing connector; for solid and stranded conductors; max. 4 mm²; 8-conductor; transparent housing; light gray cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent | PUSH WIRE® splicing connector; for solid and stranded conductors; max. 4 mm²; 3-conductor; transparent housing; orange cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent | PUSH WIRE® splicing connector; for solid and stranded conductors; max. 4 mm²; 4-conductor; transparent housing; red cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent |
|                                                                                                                |                                                                                                                    |                                                                                                                                                                                                  |                                                                                                                                                                                               |
| <a href="#">Item No.: 2773-405</a>                                                                                                                                                               | <a href="#">Item No.: 2773-406</a>                                                                                                                                                                   |                                                                                                                                                                                                  |                                                                                                                                                                                               |
| PUSH WIRE® splicing connector; for solid and stranded conductors; max. 4 mm²; 5-conductor; transparent housing; yellow cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent | PUSH WIRE® splicing connector; for solid and stranded conductors; max. 4 mm²; 6-conductor; transparent housing; Gray cover; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent       |                                                                                                                                                                                                  |                                                                                                                                                                                               |

Physical data

|        |                        |
|--------|------------------------|
| Width  | 260 mm / 10.236 inches |
| Height | 63 mm / 2.48 inches    |
| Depth  | 155 mm / 6.102 inches  |

Material data

|                      |                                                                          |
|----------------------|--------------------------------------------------------------------------|
| Note (material data) | <a href="#">Information on material specifications can be found here</a> |
| Fire load            | 5.49 MJ                                                                  |
| Weight               | 1006.4 g                                                                 |



| Commercial data       |  |               |
|-----------------------|--|---------------|
| ETIM 8.0              |  | EC000446      |
| ETIM 7.0              |  | EC000446      |
| PU (SPU)              |  | 1 pcs         |
| Packaging type        |  | Box           |
| Country of origin     |  | DE            |
| GTIN                  |  | 4055143951319 |
| Customs tariff number |  | 85369010000   |

| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 887-954

↓