



Color: ■ black

Locking system WINSTA® MINI

The locking system from the WINSTA® MINI product line guarantees you the greatest flexibility in electrical installation. An extensive range of accessories complements the WINSTA® product line from WAGO. WINSTA® MINI follows the trend towards miniaturisation. Our smallest pluggable connection system is very good for lights, for instance, since due to LED technology, these offer less and less space for the connection technology.

WINSTA® MINI solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System is ideally tailored to the strict requirements of building installation. It makes electrical installation pluggable, and thus more efficient, even more reliable, and error-free. Use of this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismatching from WAGO makes the installation of electrical components significantly easier.

- easy tool-free operation, a wide range of coding options
- fast, secure installation

| Connection data |                       |
|-----------------|-----------------------|
| Connection 1    |                       |
| Actuation type  | Finger-operated lever |

| Mechanical data |                                     |
|-----------------|-------------------------------------|
| Suitable        | for flying leads; manually operated |

| Material data               |  |
|-----------------------------|--|
| Note (material data)        | <a href="#">Information on material specifications can be found here</a> |
| Color                       | black  |
| Insulation material         | Polyamide (PA66)   |
| Flammability class per UL94 | V0   |
| Fire load                   | 0.019 MJ   |
| Weight                      | 0.6 g  |



| Environmental requirements               |  |
|--|--|
| Processing temperature                   | -5 ... +40 °C                              |
| Continuous operating temperature         | -35 ... +85 °C                             |
| Note on continuous operating temperature | Insulating parts for temperatures ≤ 105 °C |

| Commercial data       |               |
|-----------------------|---------------|
| eCl@ss 10.0           | 27-44-06-92   |
| eCl@ss 9.0            | 27-44-06-92   |
| ETIM 8.0              | EC002863      |
| ETIM 7.0              | EC002863      |
| PU (SPU)              | 100 (50) pcs  |
| Packaging type        | Box           |
| Country of origin     | DE            |
| GTIN                  | 4055143356930 |
| Customs tariff number | 85389099990   |

| Environmental Product Compliance |                         |
|----------------------------------|-------------------------|
| RoHS Compliance Status           | Compliant, No Exemption |

Approvals / Certificates

Approvals for marine applications



| Approval              | Standard | Certificate Name |
|-----------------------|----------|------------------|
| LR<br>Lloyds Register | EN 61535 | 08/20047 (E2)    |

Downloads

Environmental Product Compliance

| Compliance Search                        |                   |
|--|-------------------|
| Environmental Product Compliance 890-101 | <a href="#">↓</a> |

Documentation

| Bid Text |            |                 |                   |
|----------|------------|-----------------|-------------------|
| 890-101  | 19.02.2019 | xml<br>2.62 KB  | <a href="#">↓</a> |
| 890-101  | 13.04.2017 | doc<br>21.50 KB | <a href="#">↓</a> |



| CAD/CAE-Data  |   |
|---|---|
| CAD data  | CAE data  |
| 2D/3D Models 890-101  | ZUKEN Portal 890-101  |
|  |  |